




JCT620AH 20A SCR

Rev.A.1.1

With high ability to withstand the shock loading of large current, JCT620AH SCR provides high dV/dt rate with strong resistance T_w 9 0 0 1 T_f 0.004 T_c -0004 8 750.24 T_m



[(R)-87 (e)-99R w (s)Tj vide






FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-

Order code	Voltage V_{DRM}/V_{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
JCT620AH	600	15	TO-220A(Ins)	50	Tube

A. Tw 4 TjQ q01886 68199 0.41 6 52.15 6 f 5W n4.288 >>BDC -0.006 201 68201 re0.5(1)]TJ



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd. Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.