



JST23H-8A 25A TRIAC

Rev.A.1.1

DESCRIPTION:

The JST23H-8A triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. Compared to traditional triacs, JST23H-8A provides a very high switching capability up to junction temperatures of 150 °C. By using an internal ceramic pad, JST23H-8A provides a rated insulation voltage of 2500 VRMS, complying with UL standards (File ref: E252906). Package TO-220A is RoHS compliant.

MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
-----------	--------	-------	------

Average gate power dissipation (T _j =150)	P _{G(AV)}	1	W
Peak gate power	P _{GM}	10	W
Peak pulse voltage (T _j =25 ; non-repetitive,off-state;FIG.7)	V _{pp}	2	kV

ELECTRICAL CHARACTERISTICS (T_j=25 unless otherwise specified)

Symbol	Test Condition	Quadrant	Value	Unit
--------	----------------	----------	-------	------

I.48 re f Tw 8.046.48Tm31 0.99.4 0i

ORDERING INFORMATION

J	ST	23	H	-8	A
JieJie Microelectronics Co., Ltd.	Triacs	$I_{T(RMS)}:25A$		8: V_{DRM} / V_{RRM} 800V	A:TO-220A(Ins)
			High junction temperature		

MARKING




FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature


Inductive and resistive loads to IEC-61000-4-5 standards

IEC 61000-4-5 Standards

Surge Generator

10/50 μ S voltage surge

20/20 μ S current surge




ORDERING INFORMTON

Order coe	Voltage $V_{\text{DRM}}/V_{\text{RRM}}$ (V)	IGT(m)	Packag	Base qty. (p	Deliver mode
		- -			
JST23H-8	800	50	TO-220A(In)	50	Tube

Dument Rviitor

Dte	Revision	Cnge
Apr	A.1.0	Lasated
Oct	A.1.1	Rvise CAE ECHANALDA

PACKAGE MECHANICAL DATA



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.