



Peak pulse voltage ( $T_j=25$ ; non-repetitive, of state; FIG.8)	$V_{pp}$	4.5	kV
---	----------	-----	----

ELECTRICAL CHARACTERISTICS ( $T_j=25$  unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
$I_{GT}$	$V_D = 12V$ $R_L = 33$	- -	MAX.	10	mA
$V_{GT}$		- -	MAX.	1	V
$V_{GD}$	$V_D = V_{DRM}$ $T_j = 125$ $R_L = 3.3K$	- -	MIN.	0.2	V
$I_L$	$I_G = 1.2I_{GT}$	-	MAX.	25	mA
				30	
$I_H$	$I_T = 500mA$		MAX.	20	mA
$dV/dt$	$V_D = 540V$ Gate Open $T_j = 125$		MIN.	500	V/ $\mu s$
$(dI/dt)_c$	$(dV/dt)_c = 0V/\mu s$ , $T_j = 125$		MIN.	3	A/ms

ORDERING INFORMATION


AC 16RIN(NF6)]TJ 0 Tw5126ERI >BD271-1.

**ACJT1210-8E**

**FIG.7:** Relative variations of gate trigger current, holding current and latching current versus junction temperature


---

FIG.8 Test circuit for inductive and resistive loads to 100-5 standards






PACKAGE MECHANICAL DATA



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	9.90		10.20	0.390		0.402
B	14.70		15.80	0.579		0.622
C	9.40		9.60	0.37		0.378
D	2.40		2.70	0.094		0.106
E	1.20		1.50	0.047		0.059
F	0.75		0.85	0.029		0.033
G	1.00		1.50	0.039		0.059
H	4.40		4.70	0.173		0.185
J	2.30		2.70	0.091		0.106
K	0.38		0.55	0.015		0.022
L	0	0.10	0.25	0	0.004	0.010
M	1.25		1.35	0.049		0.053
P	1.20		1.50	0.047		0.059

FOOTPRINT TO-263 (dimensions in mm)





Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright ' 2023 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.