

DESCRIPTION:

The JST06A-800B triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. By using an internal ceramic pad, JST06A-800B provides a rated insulation voltage of 2500 VRMS, complying with UL standards (File ref: E252906). Package TO-220A is RoHS compliant.

MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	
Operating junction temperature range	T_j	-40-125	
Repetitive peak off-state voltage ($T_j=25^\circ\text{C}$)	V_{DRM}	800	V
Repetitive peak reverse voltage ($T_j=25^\circ\text{C}$)	V_{RRM}	800	V
RMS on-state current ($T_c 0100^\circ\text{C}$)	$I_{T(RMS)}$	6	A

Non repetitive surge peak on-state current 174A [(U

ORDERING INFORMATION

J	ST	06	A	-800	B
JieJie Microelectronics Co., Ltd.	Triacs	$I_T(\text{RMS}):6\text{A}$	A:TO-220A(Ins)	800:V _{DRM} /V _{RRM} 1800V	B:I _{GT1-3} 050mA I _{GT4} 070mA

MARKING



	<table><tr><td></td><td><u>XXX</u></td><td><u>XXX</u></td><td></td></tr><tr><td>Year</td><td rowspan="2"> </td><td rowspan="2"> </td><td rowspan="2">Production Code</td></tr><tr><td>Month</td></tr></table>		<u>XXX</u>	<u>XXX</u>		Year			Production Code	Month
	<u>XXX</u>	<u>XXX</u>								
Year			Production Code							
Month										

FIG.1: Maximum power dissipation versus RMS on-state current

FIG.2: RMS on-state current versus case temperature

FIG.7 ÖTest circuit for inductive and resistive loads to IEC-61000-4-5 standards



ORDERING INFORMATION

Order code	Voltage V _{DRM} /V _{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.