



for general purpose AC  
 FF function in applications  
 motor starting circuits,  
 nmers, motor speed  
 ess triac is especially  
 ads. By using an external  
 vides a rated insulation  
 h UL standards (File ref:  
 S compliant.

	Symbol	Value	Unit
	$T_{stg}$	-40-150	
(-25 )	$V_{DRM}$	800	V
(25 )	$V_{RRM}$	800	V









**FIG.1:** Maximum power dissipation versus RMS on-state current

---

**FIG.2:** RMS on-state current versus case temperature

FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards







Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.