



JST24A-1200CW 25A TRIAC

Rev.A.1.1

DESCRIPTION:

The JST24A-1200CW triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. JST24A-1200CW snubberless triac is especially recommended for use on inductive loads. By using an internal ceramic pad, JST24A-1200CW provides a rated insulation voltage of 2500 VRMS, complying with UL standards (File ref: E252906). Package TO-220A is RoHS compliant.


MAIN FEATURES

0 ABSOLUTE MAXIMUM(RATING2 6 -) G (


JST24A-1200CW

Average gate power dissipation ($T_j=125$)	$P_{G(AV)}$	0.5	W
Peak gate power	P_{GM}	10	W
Peak pulse voltage ($T_j=25$; non-repetitive, off-state; FIG.7)	V_{pp}	2.5	kV

ORDERING INFORMATION



MARKING



JST24A-1200CW

FIG.1: Maximum power dissipation vs on-state current





FIG.2: RMS on-state current vs case temperature 0510152025303

FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards



ORDERING INFORMATION

Order code	Voltage $V_{DRM}/V_{RRM}(V)$	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
-------------------	--	----------------	----------------	----------------------------	--------------------------

