



Peak pulse ( $T = \dots$ ; non-repetitive; FIG. 7)	$V_{pp}$	2.5	V
---	----------	-----	---

ELECTRICAL CHARACTERISTICS (unless specified)

Symbol	Test Condition	Quadrant	Value	Unit
$I_{GT}$	$V_D = \dots$ $L = \dots$	$\begin{matrix} - & - \\ 12V & R & 33 \end{matrix}$	MAX . 35	mA

ORDERING INFORMATION

FIG.1: Main power dissipation RMS  
on - ~~st~~ current



FIG.2: RMS on - ~~st~~ current as  
temperature



## ORDERING INFORMATION


Order code	Voltage $V_{DRM}/V_{RRM}(V)$	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		H I- J			
<b>JST24C-800CW</b>	<b>800</b>	<b>35</b>	<b>TO-220C</b>	<b>50</b>	<b>Tube</b>

PACKAGE MECHANICAL DATA



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of any omissions or errors in this document, or for any changes in the information contained herein without notice, apart from those arising from an agreement signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document precedes and replaces all information previously applied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.